Cat[®] H120 GC S Hammer



Cat® Hammers make quick work of demolition, construction, and quarrying tasks.

Combine the simple, lightweight design of the GC S Hammer series with the reliability, durability, and value you expect from Cat products. The result is a low cost-per-hour solution providing the consistent power and performance you need.

© 2022 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

LET'S DO THE WORK.

GAINWELL

Performance Series: GC Silenced

Performance	Protection	Product Support	Profitability
 Industry Standard Production Gas Fired Design Piston stroke adjuster. Versatility for different applications 	 Buffer system protects carrier from reflective forces Accumulator protects carrier hydraulic pumps from spiking Auto shut off protects hammer from blank firing Silenced as standard Auto – Lube system protects hammer from pre-mature failures: Optional 	 Cat Dealer Support Caterpillar Systems Support Caterpillar Support 	 Contractors: Daily, Weekly, Monthly, Annually Dealers: Rental Fleets, Retail Business

Specifications

H120 GC S

Mount		
Energy Class	4000 J	2,950 ft-lb
Blows per Minute	400 min	800 max
Minimum Operating Weight	1754 kg	3,859 lb
Maximum Operating Weight	1785 kg	3,927 lb
Minimum Rated Flow	125 L/min	33 gal/min
Maximum Rated Flow	151 L/min	40 gal/min
Minimum Operating Pressure	16 000 kPa	2,320 psi
Maximum Operating Pressure	18 000 kPa	2,610 psi
Tool Shaft Diameter	135 mm	5.31 in
Minimum Carrier Weight	18 t	39,683 lb
Maximum Carrier Weight	25 t	55,115 lb

 TOLL FREE NO.
 : 18004193356

 MISSED CALL NO.
 : 0808 111 2244

 EMAIL US
 : marketing@gainwellindia.com

 VISIT US
 : www.gainwellindia.com

